Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	: OPTONICA
--------------------------------	------------

Supplier's address: Anatolii Lazarov, Mitr. Serafim Slivenski, Mladost 1 144, 1784 Sofia, BG

Model identifier: 1837

_	•			
Tyna	At I	lıσht	source	٠.
IVDC	U I 1	IIGIIL	Jource	

	Product na	·	
Anti-glare shield:	No	Dimmable:	No
High luminance light source:	No		
Colour-tuneable light source:	No	Envelope:	-
Mains or non-mains:	MLS	Connected light source (CLS):	No
(or other electric interface)			
Light source cap-type	E27		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Product parameters

Parameter		Value	Parameter	Value
		General product p	arameters:	
	nption in on- 00 h), rounded st integer	15	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 320 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	25003000
On-mode pow pressed in W	ver (P _{on}), ex-	15,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen- sions without	Height	122	Spectral power distribution in the	See image in last page
separate con- trol gear, light- ing control	Width Depth	65 65	range 250 nm to 800 nm, at full-load	III iast þage

parts and non- lighting con- trol parts, if any (millime-			
tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,463
		nates (x and y)	0,420
Parameters for LED and OLED lig	ght sources:		
R9 colour rendering index value	5	Survival factor	0,90
the lumen maintenance factor	0,95		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	0,3	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;

